



POWERACT Rope

2


1. Tower Crane




POWERACT 28, 28P




POWERACT 28D, 28DP



POWERACT 29, 29P




POWERACT 25D, 25DP




POWERACT 19

2. Deck Crane



POWERACT 4

3. Special Crane



POWERACT 17D

© Properties



COMPACTED



NON-ROTATING



PLAST



1. Tower Crane

POWERACT 28, 28P

Nominal Dia.		Minimum Breaking Load (Metric Ton)		Approx Weight
		200 kg/mm ²	220 kg/mm ²	
mm	inch	1960 N/mm ²	2160 N/mm ²	Kg/m
14		18.6	19.8	0.94
14.3	9/16	19.4	20.7	0.98
15		21.4	22.7	1.08
16	5/8	24.3	25.9	1.23
17.5	11/16	29.1	30.9	1.47
18		30.7	32.7	1.55
19	3/4	34.3	36.5	1.73
20		38.0	40.4	1.92
21	13/16	41.9	44.6	2.12
22		45.9	48.9	2.32
22.2	7/8	46.9	49.9	2.37
24	15/16	54.7	58.2	2.76
25		59.3	63.1	3.00
25.4	1	61.2	65.2	3.09
26		64.2	68.3	3.24
28		74.4	79.2	3.76
30		85.4	90.9	4.32
32		97.2	103.4	4.91
34		109.7	116.8	5.54
36		123.0	130.9	6.22

POWERACT 28D, 28DP

Nominal Dia.		Minimum Breaking Load (Metric Ton)		Approx Weight
		200 kg/mm ²	220 kg/mm ²	
mm	inch	1960 N/mm ²	2160 N/mm ²	Kg/m
14		19.4	20.8	0.97
14.3	9/16	20.2	21.7	1.01
15		22.2	23.9	1.12
16	5/8	25.3	27.1	1.27
17.5	11/16	30.2	32.5	1.52
18		32.0	34.4	1.61
19	3/4	35.6	38.3	1.79
20		39.5	42.4	1.98
21	13/16	43.5	46.8	2.19
22		47.8	51.3	2.40
22.2	7/8	48.8	52.4	2.45
24	15/16	56.9	61.1	2.86
25		61.7	66.3	3.10
25.4	1	63.7	68.4	3.20
26		66.7	71.7	3.35
28		77.4	83.1	3.89
30		88.9	95.4	4.47
32		101.1	108.5	5.08
34		114.1	122.5	5.74
36		127.9	137.4	6.43

POWERACT 29, 29P

Nominal Dia.		Minimum Breaking Load (Metric Ton)		Approx Weight
		200 kg/mm ²	220 kg/mm ²	
mm	inch	1960 N/mm ²	2160 N/mm ²	Kg/m
14		18.7	19.9	0.95
14.3	9/16	19.5	20.8	0.99
15		21.5	22.8	1.09
16	5/8	24.4	26.0	1.24
17.5	11/16	29.2	31.0	1.48
18		30.8	32.8	1.56
19	3/4	34.4	36.6	1.74
20		38.1	40.5	1.93
21	13/16	42.0	44.7	2.13
22		46.0	49.0	2.33
22.2	7/8	47.0	50.0	2.38
24	15/16	54.8	58.3	2.77
25		59.4	63.2	3.01
25.4	1	61.3	65.3	3.10
26		64.3	68.4	3.25
28		74.5	79.3	3.77
30		85.0	91.0	4.33
32		97.0	103.0	4.92
34		109.0	116.0	5.56
36		123.0	131.0	6.23

POWERACT 25D, 25DP

Nominal Dia.		Minimum Breaking Load (Metric Ton)		Approx Weight
		200 kg/mm ²	220 kg/mm ²	
mm	inch	1960 N/mm ²	2160 N/mm ²	Kg/m
14		18.7	20.2	1.00
14.3	9/16	19.5	21.1	1.04
15		21.5	23.2	1.16
16	5/8	24.4	26.4	1.33
17.5	11/16	29.2	31.5	1.59
18		30.9	33.4	1.68
19	3/4	34.4	37.2	1.85
20		38.2	41.2	2.08
21	13/16	42.1	45.4	2.25
22		46.2	49.9	2.49
22.2	7/8	47.1	50.9	2.54
24	15/16	55.0	59.3	2.90
25		59.6	64.4	3.15
25.4	1	61.5	66.5	3.25
26		64.5	69.7	3.41
28		74.8	80.8	3.95
30		85.8	92.7	4.54
32		97.6	105.5	5.16
34		110.2	119.1	5.83
36		123.6	133.5	6.53

POWERACT 19

Nominal Dia.		Minimum Breaking Load (Metric Ton)			Approx Weight
		180 Kg/mm ²	200 Kg/mm ²	220 Kg/mm ²	
mm	inch	1770 N/mm ²	1960 N/mm ²	2160 N/mm ²	Kg/m
16	5/8	19.3	21.3	22.7	1.11
17.5	11/16	23.1	25.5	27.1	1.33
18		24.4	27.0	28.7	1.41
19	3/4	27.2	30.1	32.0	1.57
20		30.1	33.3	35.4	1.74
22		36.4	40.3	42.9	2.10
24		43.4	48.0	51.0	2.50
25		47.1	52.1	55.4	2.72
26		50.9	56.3	59.9	2.94
28		59.0	65.3	69.4	3.41
28.6	1-1/8	61.6	68.2	72.5	3.56
30	1-3/16	67.8	75.0	79.7	3.91

**2. Deck Crane****POWERACT 4**

Nominal Dia.		Minimum Breaking Load (Metric Ton)		Approx Weight
		180 kg/mm ²	200 kg/mm ²	
mm	inch	1770 N/mm ²	1960 N/mm ²	Kg/m
16	5/8	20.6	22.5	1.20
18	11/16	26.1	28.5	1.52
19	3/4	29.1	31.7	1.69
20		32.2	35.2	1.88
22		39.0	42.5	2.27
24	15/16	46.4	50.6	2.70
26		54.5	59.4	3.17
28		63.2	68.9	3.68
30	1-3/16	72.5	79.1	4.22
32		82.5	90.0	4.81
34		93.1	101.6	5.43

3. Special Crane**POWERACT 17D**

Nominal Dia.		Minimum Breaking Load (Metric Ton)			Approx Weight
		180 Kg/mm ²	200 Kg/mm ²	220 Kg/mm ²	
mm	inch	1770 N/mm ²	1960 N/mm ²	2160 N/mm ²	Kg/m
14		17.2	19.1	21.1	0.98
14.3	9/16	17.9	19.9	22.0	1.02
15		19.7	21.9	24.2	1.13
16	5/8	22.5	24.9	27.6	1.28
17.5	11/16	26.9	29.8	33.0	1.53
18		28.4	31.6	34.9	1.62
19	3/4	31.7	35.2	38.9	1.81
20		35.1	39.0	43.1	2.00
22	3/5	42.4	47.2	52.1	2.42
24	15/16	50.5	56.1	62.0	2.88
25		54.8	60.9	67.3	3.13
26		59.3	65.9	72.8	3.38
28		68.8	76.4	84.4	3.92