


4xSeS39



4xSeS48

Swaged Single Wire Rope (Uni Rope)

Construction 4 x SeS39 + FC | 4 x SeS48 + FC

Rope Diameter (mm)	Minimum Breaking Load [kN (ton)]				Approx. Weight			
	4xSeS39		4xSeS48		4xSeS39		4xSeS48	
	Grade B 1770N/mm ²	Grade C 1910N/mm ²	Grade B 1770N/mm ²	Grade C 1910N/mm ²	kg/m	lb/ft	kg/m	lb/ft
8	40.9 (4.17)	44.3 (4.52)	-	-	0.262	0.18	-	-
9	41.8 (5.28)	56.1 (5.72)	-	-	0.330	0.22	-	-
10	63.9 (6.52)	69.2 (7.06)	-	-	0.410	0.28	-	-
11.2	80.3 (8.19)	86.8 (8.85)	-	-	0.514	0.35	-	-
12	89.0 (9.08)	100 (10.2)	-	-	0.590	0.40	-	-
12.5	100 (10.2)	108 (11.0)	-	-	0.640	0.43	-	-
14	126 (12.9)	136 (13.9)	-	-	0.800	0.54	-	-
16	164 (16.7)	177 (18.1)	164 (16.7)	189 (19.3)	1.04	0.70	1.00	0.67
18	208 (21.2)	224 (22.8)	209 (21.3)	239 (24.4)	1.34	0.90	1.27	0.85
19	231 (23.6)	250 (25.5)	231 (23.6)	266 (27.1)	1.49	1.00	1.41	0.95
20	256 (26.1)	277 (28.3)	256 (26.1)	295 (30.1)	1.63	1.10	1.56	1.05
22	310 (31.6)	335 (34.2)	310 (31.6)	357 (36.4)	1.97	1.32	1.89	1.27
22.4	321 (32.8)	347 (35.4)	322 (32.8)	370 (37.7)	2.04	1.37	1.96	1.32
24	356 (36.3)	399 (40.7)	356 (36.3)	425 (43.4)	2.35	1.58	2.25	1.51
25	399 (40.7)	433 (44.2)	399 (40.7)	450 (45.9)	2.55	1.71	2.44	1.64
26	432 (44.1)	468 (47.7)	432 (44.1)	487 (49.7)	2.76	1.85	2.64	1.77
28	502 (51.2)	543 (55.4)	502 (51.2)	564 (57.5)	3.25	2.18	3.07	2.06
30	576 (58.8)	623 (63.5)	576 (58.8)	648 (66.1)	3.73	2.51	3.52	2.37
31.5	635 (64.8)	687 (70.1)	635 (64.8)	714 (72.8)	4.11	2.76	3.88	2.61
32	655 (66.8)	709 (72.3)	655 (66.8)	737 (75.2)	4.24	2.85	4.00	2.69
33.5	718 (73.2)	777 (79.3)	718 (73.2)	808 (82.4)	4.65	3.12	4.39	2.95
34	740 (75.4)	800 (81.6)	740 (75.4)	812 (82.8)	4.79	3.22	4.52	3.04
35.5	806 (82.2)	872 (88.9)	806 (82.2)	885 (90.3)	5.22	3.51	4.93	3.31
36	829 (84.6)	897 (91.5)	829 (84.5)	910 (92.8)	5.37	3.61	5.07	3.41
37.5	900 (91.8)	974 (99.3)	899 (91.7)	938 (95.7)	5.83	3.92	5.50	3.70
38	924 (94.2)	1000 (102)	924 (94.2)	954 (97.3)	5.98	4.02	5.65	3.80

※ Read important warnings on preceding pages.