



6xWS26+IWRC



6xWS31+IWRC



6xWS36+IWRC

## Swaged Wire Rope

Construction 6xWS26+IWRC | 6xWS31+IWRC | 6xWS36+IWRC

Rope Diameter		Minimum Breaking Load [ kN (ton) ]		Approx. Weight	
		Normal Swaged			
mm	inch	1910N/mm <sup>2</sup>		kg/m	lb/ft
8	-	55.8	(5.69)	0.329	0.22
9	-	70.6	(7.20)	0.426	0.29
9.53	3/8	78.6	(8.02)	0.463	0.31
10	-	87.1	(8.88)	0.500	0.34
11.11	7/16	109	(11.1)	0.620	0.42
12	-	125	(12.8)	0.730	0.49
12.7	1/2	141	(14.4)	0.828	0.56
14	-	169	(17.2)	1.010	0.68
14.29	9/16	176	(18.0)	1.050	0.71
15.88	5/8	214	(21.8)	1.270	0.85
16	-	218	(22.2)	1.29	0.87
18	-	276	(28.2)	1.65	1.11
19.05	3/4	310	(31.6)	1.86	1.25
20	-	344	(35.1)	2.06	1.38
22	-	416	(42.4)	2.49	1.67
22.23	7/8	421	(42.9)	2.55	1.71
24	-	488	(49.8)	2.97	2.00
25	-	518	(52.8)	3.22	2.16
25.4	1	534	(54.5)	3.32	2.23
26	-	559	(57.0)	3.48	2.34
28	-	610	(62.2)	4.04	2.71
28.58	1 1/8	636	(64.9)	4.21	2.83

※ Read important warnings on preceding pages.