

PP Leded Rope

Length : 190 m

| Dia (mm) | Weight (kg) | M.B.L (ton) | |
|----------|-------------|-------------|---------|
| | | HI MAN | Manline |
| 8 | 9.5 | 0.99 | 0.77 |
| 9 | 12.0 | 1.19 | 0.95 |
| 10 | 15.0 | 1.40 | 1.15 |
| 12 | 21.0 | 2.00 | 1.62 |
| 14 | 28.5 | 2.60 | 2.16 |
| 16 | 37.5 | 3.30 | 2.70 |
| 18 | 48.0 | 4.20 | 3.42 |
| 20 | 59.0 | 4.90 | 4.10 |
| 22 | 71.0 | 5.90 | 5.04 |
| 24 | 82.5 | 6.80 | 5.85 |
| 26 | 99.0 | 7.90 | 6.75 |
| 28 | 115 | 9.10 | 7.65 |
| 30 | 127 | 10.3 | 8.90 |
| 32 | 142 | 11.5 | 9.90 |
| 34 | 163 | 13.0 | 11.2 |
| 36 | 182 | 14.4 | 12.3 |
| 38 | 203 | 15.9 | 13.6 |
| 40 | 225 | 17.4 | 15.0 |

- It sinks under the water as containing about 30% of lead.
- Special leads are being used so it is not exposed out side.
- Lead ratio can be adjustable according to request.

Polytex Rope

Length : 200 m

| Dia (mm) | Weight (kg) | M.B.L (ton) |
|----------|-------------|-------------|
| 4 | 1.70 | 0.20 |
| 5 | 2.65 | 0.30 |
| 6 | 3.83 | 0.40 |
| 8 | 6.78 | 0.70 |
| 9 | 8.51 | 0.90 |
| 10 | 10.6 | 1.10 |
| 12 | 15.7 | 1.42 |
| 14 | 20.3 | 1.90 |
| 16 | 26.6 | 2.43 |
| 18 | 34.0 | 3.03 |
| 20 | 42.3 | 3.68 |
| 22 | 50.8 | 4.40 |
| 24 | 61.4 | 5.17 |
| 26 | 71.0 | 6.00 |
| 28 | 82.5 | 6.88 |
| 30 | 95.0 | 7.83 |
| 32 | 107 | 8.82 |
| 34 | 121 | 9.88 |

- Less slip as it is combined with 70% of polyethylene and 30% of vinylon. (or polyester spun)
- Polyethylene contents can be adjustable.

6-Strand Compound Rope

| Wire St. Const. | | 1 x 12 | | 1 x 19 | | 1 x 24 | |
|-----------------|--------------------|-------------|-----------------|-------------|-----------------|-------------|-----------------|
| Rope Dia. (mm) | Wire St. Dia. (mm) | PP W t (kg) | Vynlon W t (kg) | PP W t (kg) | Vynlon W t (kg) | PP W t (kg) | Vynlon W t (kg) |
| 16 | 2.7 | 50 | 55 | 71 | 76 | 62 | 68 |
| 18 | 3.0 | 63 | 69 | 84 | 91 | 79 | 85 |
| 20 | 3.3 | 78 | 86 | 103 | 111 | 97 | 105 |
| 22 | 4.0 | 103 | 112 | 141 | 150 | 124 | 134 |
| 24 | 4.7 | 132 | 142 | 181 | 191 | 161 | 172 |
| 26 | 5.3 | 165 | 177 | 226 | 238 | 202 | 213 |
| 28 | 6.0 | 202 | 215 | 273 | 286 | 252 | 264 |
| 30 | 6.7 | 243 | 257 | 342 | 355 | 310 | 323 |
| 32 | 7.3 | 288 | 303 | 391 | 406 | 365 | 380 |
| 34 | 8.0 | 337 | 353 | 462 | 478 | 433 | 449 |
| 36 | 8.3 | 370 | 388 | 505 | 524 | 459 | 478 |
| 38 | 8.7 | 406 | 427 | 553 | 574 | 504 | 524 |
| 40 | 10.0 | 507 | 526 | 729 | 749 | 665 | 684 |

- Strand diameters and constructions are adjustable according to request.