



## 8 x 19 Class Wire Rope ( Fiber Core )


► For Elevator ( Hoist and Governor )



**8x19 Seale  
Fiber Core  
( 8 x 9/9/1 )**



**8x19 Warrington  
Fiber Core  
( 8 x 6 & 6/6/1 )**



**8x19 Filler  
Fiber Core  
( 8 x 12/6 & 6F/1 )**

### JIS G 3525

Diameter Of Rope		Minimum Breaking Load						Approx. Mass per Meter  Kg/m
		Ungalvanized						
		1320/mm <sup>2</sup> ( 135kgf/mm <sup>2</sup> )		1620/mm <sup>2</sup> ( 165kgf/mm <sup>2</sup> )		1770/mm <sup>2</sup> ( 180kgf/mm <sup>2</sup> )		
mm	Approx. inch	kN	tf	kN	tf	kN	tf	
8	5/16	26.0	2.65	30.8	3.14	32.8	3.35	0.220
9	3/8	32.9	3.36	39.0	3.97	41.5	4.23	0.278
10	13/32	40.6	4.14	48.1	4.90	51.3	5.23	0.343
11	7/16	49.2	5.01	58.2	5.93	62.0	6.32	0.415
12	15/32	58.5	5.96	69.2	7.06	73.8	7.53	0.494
12.5	1/2	63.5	6.47	75.1	7.66	80.1	8.17	0.536
13	33/64	68.6	7.00	81.3	8.29	86.6	8.83	0.580
14	9/16	79.6	8.12	94.3	9.61	100	10.2	0.672
15	19/32	91.4	9.32	108	11.0	115	11.8	0.772
16	5/8	104	10.6	123	12.6	131	13.4	0.878
18	23/32	132	13.4	156	15.9	166	16.9	1.11
20	13/16	162	16.6	192	19.6	205	20.9	1.37
22	7/8	197	20.0	233	23.7	248	25.3	1.66
24	15/16	234	23.9	277	28.2	295	30.1	1.98
25	1	254	25.9	301	30.6	320	32.7	2.14